



Contact Information

USA

405 Barclay Blvd.
Lincolnshire, IL 60069
USA

Toll free: +1.800.538.0363
Tel: +1.847.955.8200
Fax: +1.847.955.8210

HA_customerservice@honeywell.com
www.honeywellanalytics.com

Canada

Calgary Office

2840 2nd Ave SE
Calgary, Alberta, Canada
T2A 7X9

Brossard Office

3580 Rue Isabelle Unit 100
Brossard, Quebec, Canada
J4Y 2R3

Toll free: +1.800.538.0363
Tel: +1.847.955.8200
Fax: +1.847.955.8210

Latin & South America

Marginal da Rodovia dos Bandeirantes, 100
Distrito Industrial
Jundiaí, São Paulo – Brazil
ZIP: 13213-008

Tel: +55 11 3309 1030
Fax: +55 11 3309 1005
Email: ha.latinamerica@honeywell.com

Customer Service and Application Support

Product and Application Support

855-955-EXPERT (855-955-3973)
analytics.industrial.sales@honeywell.com

Customer Service Representatives

855-955-EXPERT (855-955-3973)
ha_customerservice@honeywell.com

Table of Contents



- FSX Detectors**
 - Quick Reference Chart 2
 - Applications Chart 3
 - Model FS24X 4
 - Model FS20X 6

- SSX Detectors**
 - Applications Chart 8
 - Quick Reference Chart 9
 - SS4-A2 & AS Series 10
 - SS4-AUV Series 12
 - SS3 Series 13
 - SS2-A Series 14
 - SS2-AM Series 15

- FS Detectors**
 - Model FS7 16
 - FS10 Fire Detection Systems 18

- Service**
 - Honeywell Analytics Service 21

Note
Specifications and exact product offering are subject to change without notice. This publication is not intended to form the basis of a contract.

FSX Detectors

Quick Reference Chart

	FS24X-2	FS24X-9	FS20X	FS10
SPECTRAL SENSITIVITY	Ultraviolet Band (0.18 – 0.26 μ)		✓	
	Visible Band (0.4 – 0.7 μ)	✓	✓	✓
	NearBand IR (0.7 μ – 1.1 μ)	✓	✓	✓
	WideBand IR1 (1.1 – 3 μ)	✓	✓	✓
	WideBand IR2 (1.1 – 7 μ)	✓	✓	
SENSITIVITY (feet)*	Very High	200+	200+	200+
	High	150	150	150
	Medium	100	100	100
	Low	50	50	50
RESPONSE	Fireball / Quick Response Option (< 500 mS)	✓	✓	✓
	Acetylene Long Range Option			✓
OTHER	Field of View (conical)	110°	90°	90°
	HART Option	✓	✓	✓
	Modbus Built-In	✓	✓	✓
ENCLOSURES	Aluminum Class, Div. 1	✓	✓	✓
	316 Stainless Steel Class I, Div. 1	✓	✓	✓
APPROVALS	FM	✓	✓	✓
	cFM	✓	✓	✓
	ATEX	✓	✓	✓
	IECEX	✓	✓	✓
	INMETRO	✓	✓	
	GOST-R			✓
	CCCF	✓	✓	
	SIL 2 Compliant	✓	✓	
TEST LAMPS	TL-2055X	✓	✓	
	TL-1055X	✓	✓	
	TL-1133X			✓
MOUNT	SM4	✓	✓	✓

*Detection distance for a one sq. ft. reference heptane pan fire

FSX Detectors

Applications Chart

		FS24X-2	FS24X-9	FS20X	FS10
FINISHING	Aerosol Filling Facilities	●	●	●	●
	Automotive Paint Lines	○	○	○	●
	Curing Ovens	○	○	○	●
	General Finishing	○	○	○	●
	Liquid Paint Spray Line	○	○	○	●
	Paint and Solvent Storage	●	●	●	●
	Powder Coating Booths	○	○	○	●
GENERAL	Aircraft Hangars	●	●	●	○
	Airport Terminals	●	●	○	○
	Cold Storage Warehouses	●	●	○	○
	Engine Test Cells	●	●	●	○
	General Warehouse	●	●	●	○
	Lumber Storage	●	●	●	○
	Marine Engine Rooms	●	●	●	○
	Marine Terminals	●	●	●	○
	Munitions	○	○	○	○
	Power Plants	●	●	○	○
OIL, GAS & PETROCHEMICALS	Acetylene Processing and Storage	○	○	●	○
	Chemical Storage	●	●	●	○
	Cogeneration Plants	●	●	●	○
	Crude and Product Tank Farms	●	●	○	○
	Ethanol Production and Storage	○	○	●	○
	Gas Collection Facilities	●	●	●	○
	Gas Compressor Buildings	●	●	●	○
	Gas Processing Plants	●	●	●	○
	Gas Turbine Enclosures	●	●	●	○
	Gasoline Loading Terminals	●	●	●	○
	Isopropanol (IPA) Production and Storage	○	○	●	○
	LNG Storage/Distribution	●	○	●	○
	LPG Storage/Distribution	●	●	●	○
	Methanol Production and Storage	○	○	●	○
	Natural Gas and CNG Plants	○	○	●	○
	Offshore Drilling Platforms	●	●	●	○
	Offshore Production Platforms	●	●	●	○
	Petrochemical Plants	●	●	●	○
	Petroleum Product Pipelines	●	●	●	○
	Petroleum Product Pumping Stations	●	●	●	○
Rail and Truck Loading/Unloading	●	●	●	○	
Refineries	●	●	●	○	
SEMICONDUCTOR	Clean Rooms	○	○	○	○
	Gas Cabinets	○	○	○	○
	Hydrogen Gas Cabinets	○	○	○	○
	Hydrogen Plants	○	○	○	○
	Hydrogen Storage	○	○	○	○
	IPA Stations	○	○	○	○
	Silane Gas Cabinets	○	○	○	○
	Silane Gas Manufacturing	○	○	○	○
	Silane Gas Storage	○	○	○	○
	Wet Benches	○	○	○	○
	Wet Chemicals	○	○	○	○

● Recommended ○ Suitable ○ Not Recommended

Model FS24X

QuadBand™ Triple IR Fire and Flame Detector
(IR/IR/IR/Visible)



The Fire Sentry FS24X is the latest generation high technology Multi-Spectrum Triple IR (IR/IR/IR/Visible) Fire and Flame Detector, which is part of our FSX family of advanced technology Electro-Optical fire detectors. Using our patented* WideBand IR™, WideBand 4.3 micron IR™, and Visible detection technology, the Fire Sentry FS24X is a quantum leap in flame and fire detection. Sophisticated software algorithms and dual microprocessors ensure that the Fire Sentry FS24X has the highest fire detection performance combined with optimal false alarm rejection.

110° field of view with a range up to 200 ft.

Features

- Patented* WideBand IR™ Technology
- Patented* Electronic Frequency Analysis™
- Visible Sensor for optimum false alarm rejection
- Selectable detection sensitivities
- Field-of-View: 110° full 100% cone-of-vision (90° full 100% cone-of-vision model also available)
- Dual microprocessors for reliable performance
- Real-time clock for accurate time dating of events
- FirePic™ — pre-fire event data storage
- Event log with date and time stamp
- RS-485 ModBus communication
- Non-Isolated 4-20 mA Analog output (sink or source)
- Alarm, Fault and Fire Verification relays
- Automatic optical path and electronic self-test
- Widest operating temperature range
- Patented* Electronics Module for components protection with easy plug-in terminations and field installation
- Two 3/4 in. NPT OR 25 mm conduit entries
- Low power consumption
- High RFI and EMI immunity
- FM, ATEX, CE mark approvals
- Meets SIL 2 requirements

Benefits

- Detects hydrocarbon fuel fires in all environmental conditions
- User selectable outputs
- Optimal false alarm rejection for all environmental conditions
- Minimal maintenance for trouble-free operation
- PC software and Interface Module (FSIM) for fault diagnostics, real-time graphics (RTGs), and downloading of FirePics™ and event log
- Suitable for a wide variety of applications
- Easy electronics module replacement
- Test lamps for manual testing

Model FS24X

QuadBand™ Triple IR Fire and Flame Detector (IR/IR/IR/Visible)

FS24X-211 Series with 110° Field of View, Standard Temp Range -40° to 85°C	Part Number
QuadBand™ IR3+ detector, copper-free aluminum encl., (2) 3/4 in. NPT entries FM and ATEX approved	FS24X-211-21-1
QuadBand™ IR3+ detector, 316 stainless steel encl., (2) 3/4 in. NPT entries FM and ATEX approved	FS24X-211-22-1
QuadBand™ IR3+ detector, copper-free aluminum encl., (2) M25 entries FM and ATEX approved	FS24X-211-23-1
QuadBand™ IR3+ detector, 316 stainless steel encl. (2) M25 entries FM and ATEX approved	FS24X-211-24-1

FS24X-911 Series with 90° Field of View, Standard Temp Range -60° to 85°C	Part Number
QuadBand™ IR3+ detector, copper-free aluminum encl., (2) 3/4 in. NPT entries FM and ATEX approved	FS24X-911-21-1
QuadBand™ IR3+ detector, 316 stainless steel encl., (2) 3/4 in. NPT entries FM and ATEX approved	FS24X-911-22-1
QuadBand™ IR3+ detector, copper-free aluminum encl., (2) M25 entries FM and ATEX approved FM and ATEX approved	FS24X-911-23-1
QuadBand™ IR3+ detector, 316 stainless steel encl. (2) 25 mm entries FM and ATEX approved	FS24X-911-24-1

Replacement Detector Modules FS24X	Part Number
211 Series standard temp range	FS24X-211-10
911 Series standard temp range	FS24X-911-10

Accessories FS24X	Part Number
Stainless steel swivel mounting assembly for FS24X, FS20X, FS10, SS4, SS2 detectors	SM4
Universal charger for Fire Sentry test lamps and interface kits. For 110-240 V _{AC} with international plugs	PSU-12
IR test lamp for testing FSX detectors, explosion proof version. Incl universal charger	TL-2055
IR test lamp for testing FSX detectors, non-explosion proof version. Incl universal charger	TL-1055
Sunshield for SS2, SS4, FS20X, and FS24X detectors, 316 stainless steel	SH-001
Field of view restrictor	FVR-01

Spare Parts FS24X	Part Number
FSX interface kit with interface module, RS485 cable, USB cable, power adapter and Windows PC software	FSX-A001
FSX interface module with RS485 cable	FSX-A002
Stainless steel grill kit for FS18X and FS24X-2 detectors	FSX-A009
Stainless steel grill kit for FS24X-9 detectors	FSX-A010
Optional HART module for FS20X and FS24X detectors (factory installed)	FSX-A014

Model FS20X

Multi-Spectrum Fire and Flame Detector
(IR/IR/UV)



The Fire Sentry FS20X is the latest generation high technology Multi-Spectrum (UV/Dual IR/VIS) Fire and Flame Detector, which is part of the FSX family of advanced technology Electro-Optical Flame detectors. Based on the foundation of the highly successful and reliable Fire Sentry SS4 detector, the Fire Sentry FS20X detector represents a quantum leap in integrating Infrared and Ultraviolet sensing technologies. The Fire Sentry FS20X is a Multi-Spectrum and UV/Dual IR/VIS fire and flame detector with a proven UV solar-blind sensor. The Fire Sentry FS20X exhibits faster false-alarm free response to fires over a wider temperature range and with a much longer detection range compared to conventional UV/IR detectors.

Solar blind 90° field of view and detection range greater than 200 ft.

Features

- Patented* WideBand IR™ Infrared combined with Ultraviolet
- Detection range greater than 200 feet to 1 sq. ft. heptane fire
- Patented* Electronic Frequency Analysis
- Visible Sensor for optimum false alarm rejection
- Selectable detection sensitivities
- Solar blind 90° full 100% cone-of-vision
- Dual Microprocessors for reliable performance
- Real-time clock for accurate time dating of events
- FirePic™ — Up to 6 pre-fire event data storage
- Event log — Up to 200 events with date and time stamp
- Built-in RS-485 ModBus Communication
- Built-in non-isolated 4-20 mA analog output (sink or source)
- Alarm, Fault and Fire Verification relays
- Automatic Optical Path and Electronic Self-Test
- Widest operating temperature range
- Patented* Electronics Module for components protection with plug-in terminations for easy field installation
- Two 3/4 in. NPT OR 25 mm conduit entries
- Low power consumption
- High RFI and EMI immunity
- FM approved

Benefits

- Detects hydrocarbon and non-hydrocarbon fuel fires in all environmental conditions
- Arc welding immunity
- False alarm rejection for all environmental conditions
- Minimal maintenance for trouble-free operation
- PC software and Interface Module (FSIM) for fault diagnostics real-time graphs (RTGs), and downloading of FirePics™ and event log
- Suitable for a wide variety of applications

Model FS20X

Multi-Spectrum Fire and Flame Detector (IR/IR/UV)

FS20X-211 Series, Standard Temp Range -40° to 85°C

Part Number

Dual IR/UV copper-free aluminum encl. with (2) 3/4 in. NPT entries, FM, cFM for Class I, Div. 1, Groups A, B, C, D; Class II, Div. 1, Groups E, F, G; Class III	FS20X-211-21-2
Dual IR/UV stainless steel encl. with (2) 3/4 in. NPT entries, FM, cFM for Class I, Div. 1, Groups A, B, C, D; Class II, Div. 1, Groups E, F, G; Class III	FS20X-211-22-2
Dual IR/UV copper-free aluminum encl. with (2) M25 entries, FM, cFM, ATEX, IECEx for Class I, Zone 1	FS20X-211-23-3
Dual IR/UV stainless steel encl. with (2) M25 entries, FM, cFM, ATEX, IECEx for Class I, Zone 1	FS20X-211-24-3

Accessories FS20X

Part Number

Optional HART module for FS18X, FS19X, FS20X, FS24X (factory installed)	FSX-A014
Stainless steel swivel mounting assembly for FS24X, FS18X, SS4, SS2 detectors	SM4
Universal charger for Fire Sentry test lamps and interface kits. For 110-240 V _{AC} with international plugs	PSU-12
IR test lamp for testing FS18X, FS20X and FS24X detectors, explosion proof version. Incl universal charger	TL-2055
IR test lamp for testing FS18X, FS20X and FS24X detectors, non-explosion proof version. Incl universal charger	TL-1055
Sunshield for SS2, SS4 and FS24X detectors, 316 stainless steel	SH-001
Field of view restrictor	FVR-01

Spare parts FS20X

Part Number

Replacement electronics module for FS20X detectors. Module only, standard temp. range	FS20X-211-10
---	--------------

SSX Detectors

Quick Reference Chart

		SS4-A	SS4-AS	SS4-AUV	SS3-A	SS2-A	SS2-AM
SPECTRAL SENSITIVITY	Ultraviolet Band (0.18 - 0.26 μ)	✓	✓	✓	✓	✓	✓
	Visible Band (0.4 - 0.7 μ)	✓	✓		✓	✓	✓
	WideBand IR (0.7 - 3.0 μ)	✓	✓		✓	✓	✓
SENSITIVITY (in feet)*	Very High	60	60	60	30	60	60
	High	45	45	45			
	Medium	30	30	30			
	Low	15	15	15			
RESPONSE	Ultra High-Speed Response (Munitions)						✓
	Ultra High-Speed Response (Sodium Azide)						✓
	Optimized Response (H4Si, H2, Alcohols, CH4)		✓				
	Standard Response	✓		✓	✓	✓	✓
OTHER	Field of View	120°	120°	120°	120°	120°	120°
	HART Option	✓	✓	✓			
	ModBus Option	✓	✓	✓			
	4-20 mA Option	✓	✓	✓			
ENCLOSURE	Aluminum	✓	✓	✓		✓	✓
	316 Stainless Steel	✓	✓	✓		✓	✓
	ABS Plastic				✓		
APPROVALS	FM	✓	✓	✓	✓	✓	✓
	cFM	✓	✓	✓	✓	✓	✓
	ATEX	✓	✓	✓			
	IECEX	✓	✓	✓			
	INMETRO	✓					
	GOST-R	✓					
	SIL 2 Compliant	✓	✓	✓			
TEST LAMP/SOURCE	FT-2145 (Explosion Proof)	✓	✓	✓	✓	✓	✓
	DD85001 (Short Range)	✓	✓	✓	✓	✓	✓
	85001			✓			
	TS2					✓	✓
MOUNT	SM4	✓	✓	✓		✓	✓
	188424				✓		

*Detection distance for a one sq. ft. reference heptane pan fire

SSX Detectors

Applications Chart

		SS4-A	SS4-AS	SS4-AUV	SS3-A	SS2-A	SS2-AM
GENERAL	Airbag Manufacturing	○	○	○	○	○	●
	Aircraft Hangars	●	●	○	○	●	○
	Airport Terminals	●	●	○	○	●	○
	Cold Storage Warehouses	●	●	●	●	●	○
	Engine Test Cells	●	●	●	●	●	○
	General Warehouse	●	●	●	●	●	○
	Lumber Storage	●	●	○	●	●	○
	Marine Engine Rooms	●	●	●	●	●	○
	Marine Terminals	●	●	○	○	●	○
	Munitions	○	○	○	○	○	●
	Power Plants	●	●	●	○	●	○
	OIL, GAS & PETROCHEMICALS	Acetylene Processing and Storage	○	●	●	○	●
Chemical Storage		●	●	●	○	●	○
Cogeneration Plants		●	●	●	○	●	○
Crude and Product Tank Farms		●	●	●	○	●	○
Ethanol Production and Storage		○	●	●	○	●	○
Gas Collection Facilities		●	●	●	○	●	○
Gas Compressor Buildings		●	●	●	○	●	○
Gas Processing Plants		●	●	●	○	●	○
Gas Turbine Enclosures		○	●	●	○	●	○
Gasoline Loading Terminals		●	●	●	○	●	○
Isopropanol (IPA) Production and Storage		○	●	●	○	●	○
LNG Storage/Distribution		○	●	●	○	●	○
LPG Storage/Distribution		●	●	●	○	●	○
Methanol Production and Storage		○	●	●	○	●	○
Natural Gas and CNG Plants		○	●	●	○	●	○
Offshore Drilling Platforms		●	●	●	○	●	○
Offshore Production Platforms		●	●	●	○	●	○
Petrochemical Plants		●	●	●	○	●	○
Petroleum Product Pipelines		●	●	●	○	●	○
Petroleum Product Pumping Stations		●	●	●	○	●	○
Rail and Truck Loading/Unloading	●	●	●	○	●	○	
Refineries	●	●	●	○	●	○	
SEMICONDUCTOR	Clean Rooms	○	●	●	●	●	○
	Gas Cabinets	○	●	●	●	○	○
	Hydrogen Gas Cabinets	○	●	●	●	○	○
	Hydrogen Plants	○	●	●	●	○	○
	Hydrogen Storage	○	●	●	●	○	○
	IPA Stations	○	●	●	●	●	○
	Silane Gas Cabinets	○	●	●	●	○	○
	Silane Gas Manufacturing	○	●	●	●	○	○
	Silane Gas Storage	○	●	●	●	○	○

● Recommended ● Suitable ○ Not Recommended

SS4-A2 & AS Series

Multi-Spectrum™ Electro-Optical Digital
Fire and Flame Detector (UV/IR)



The SS4 is a hazardous area certified flame detector for the detection of hydrocarbon (SS4-A2) and non-hydrocarbon fires (SS4-AS2). This multispectrum detector senses radiant energy in the ultraviolet (UV), visible and wideband infrared (IR) spectrum. The radiant energy from all types of flaming fires will alert the detector to their presence. The field of view is the widest in the industry with 120° field of view with a range of 60 feet. This means more hazard can be covered by each detector.

120° field of view with range up to 60 feet.

Features

- Multi-Spectrum™: senses ultraviolet, visible and Wide Band Infrared™
- Built-in test for optical “through the lens” testing
- False alarm immunity
- Detects hydrocarbon and non-hydrocarbon based fires
- Wide field-of-view and solar-blind
- Adjustable detector sensitivity
- Microprocessor based algorithms: FirePic™, Snapshot™ and Tri-Mode Plot™
- Wide temperature range of operation
- Compatible with standard approved fire alarm panels
- Explosion-proof housing
- Time programmable alarm verification

SS4-A2 & AS Series

Multi-Spectrum™ Electro-Optical Digital Fire and Flame Detector (UV/IR)

SS4-A2 & SS4-AS2	Part Number
Aluminum UV/IR, FM, hydrocarbon fires, non latching alarm LED, FM, cFM, CSFM for Class I, Div. 1 groups B, C & D (2) 3/4 in. NPT	SS4-A2
Stainless steel UV/IR, FM, hydrocarbon fires, non latching alarm LED, FM, cFM, CSFM for Class I, Div. 1 groups B, C & D (2) 3/4 in. NPT	SS4-A2-SS
Aluminum UV/IR, ATEX, hydrocarbon fires, non latching alarm LED, FM, cFM, ATEX, IECE for Zone 1 (2) 3/4 in. NPT	SS4-A2-C
Aluminum UV/IR, ATEX, hydrocarbon fires, non latching alarm LED, FM, cFM, ATEX, IECEX for Zone 1 (2) M25	SS4-A2-C-E
Stainless steel UV/IR, ATEX, hydrocarbon fires, non latching alarm LED, FM, cFM, ATEX, IECEX for Zone 1 (2) M25	SS4-A2-CSS-E
Aluminum UV/IR, ATEX, hydrogen and non hydrocarbon fires, non latching alarm LED, FM, cFM, CSFM for Class I, Div. 1 groups B, C & D (2) M25	SS4-AS2-C-E
Stainless steel UV/IR, ATEX, hydrogen and non hydrocarbon fires, non latching alarm LED, FM, cFM, ATEX, IECEX for Zone 1 (2) M25	SS4-AS2-CSS-E
Stainless steel UV/IR, ATEX, hydrocarbon fires, non latching alarm LED, FM, cFM, ATEX, IECE for Zone 1 (2) 3/4 in. NPT	SS4-A2-CSS
Aluminum UV/IR, FM, hydrogen and Non-Hydrocarbon Fires, non-latching alarm LED, FM, cFM, CSFM for Class I, Div. 1 groups B, C & D (2) 3/4 in. NPT	SS4-AS2
Stainless steel UV/IR, FM, hydrogen and Non-Hydrocarbon Fires, non-latching alarm LED, FM, cFM, CSFM for Class I, Div. 1 groups B, C & D (2) 3/4 in. NPT	SS4-AS2-SS
Aluminum UV/IR, ATEX, hydrogen and non hydrocarbon fires, non latching alarm LED, FM, cFM, CSFM for Class I, Div. 1 groups B, C & D (2) 3/4 in. NPT	SS4-AS2-C
Stainless steel UV/IR, ATEX, hydrogen and non hydrocarbon fires, non latching alarm LED, FM, cFM, ATEX, IECEX for Zone 1 (2) 3/4 in. NPT	SS4-AS2-CSS

Accessories SS4-A2 & SS4-AS2	Part Number
Stainless steel swivel mounting assembly for FS24X, FS18X and SS4 detectors	SM4
0-20 MA module for SS4 detectors new version (factory installed)	MA420-4
UV/IR test lamp with universal charger (FM and ATEX approval)	FT-2145
Interface kit for SS4 detector, with universal charger	2029-INTERFACE-KIT
Sunshield for SS2, SS4 and FS24X detectors, 316 stainless steel	SH-001
Field of view restrictor	FVR-01
SS4 module HART (factory fitted, order with detector)	SS4-FSHCOM

Spare Parts SS4-A2 & SS4-AS2	Part Number
Replacement electronics module for SS4-A2 (UV/IR) detectors. Module only, non-latching LED	SS4-MOD-A2
Replacement electronics module for SS4-AS2 (UV/IR) detectors. Module only, non-latching LED	SS4-MOD-AS2
UV test source module for SS4 detectors	H200
IR test lamp bulb (FT-2145)	LAMP-3135-0002
UV test lamp bulb (FT-2145)	DT-3124-0001A

SS4-AUV Series

UV-Spectrum™ Electro-Optical Digital Fire and Flame Detector (UV)



While retaining all the features of the standard SS4-A2, is optimized for the detection of ethanol, methanol, hydrogen and natural gas with a range up to 60 feet range and a field of view of 120°. The UV only version, SS4-AUV2, is for indoor applications where UV sources such as welding are not present.

120° field of view with range up to 60 feet.

Features

- Senses solar-blink ultraviolet band
- Built-in test for optical “through the lens” testing
- Utilizes long-life, ruggedized UV sensors
- Detects hydrocarbon and non-hydrocarbon based fires
- Wide field-of-view and solar-blind
- Adjustable detector sensitivity
- Microcomputer based algorithms: FirePic™, Snapshot™ and UV Plot
- Wide temperature range of operation
- Compatible with standard approved fire alarm panels
- Explosion-proof housing
- Time programmable alarm verification

SS4-AUV Series

	Part Number
Aluminum UV, FM, hydrocarbon and non-hydrocarbon fires, non-latching alarm LED, FM, cFM, CSFM for C1, D1, Groups B, C, D (2) 3/4 in. NPT	SS4-AUV2
Aluminum UV, FM, ATEX, hydrocarbon and non-hydrocarbon fires, non-latching alarm LED, FM, cFM, ATEX, IECEx Zone 1 (2) M25	SS4-AUV2-C
Aluminum UV, FM, ATEX, hydrocarbon and non-hydrocarbon fires, non-latching alarm LED, FM, cFM, ATEX, IECEx Zone 1 (2) M25	SS4-AUV2-C-E
Stainless steel UV, FM, ATEX, hydrocarbon and non-hydrocarbon fires, non-latching alarm LED FM, cFM, ATEX, IECEx Zone 1 (2) M25	SS4-AUV2-CSS-E
Stainless steel UV, FM, ATEX, hydrocarbon and non-hydrocarbon fires, non-latching alarm LED FM, cFM, ATEX, IECEx Zone 1 (2) M25	SS4-AUV2-CSS
Stainless steel UV, FM hydrocarbon and non-hydrocarbon fires, non-latching alarm LED, FM, cFM, CSFM for C1, D1, Groups B, C, D (2) 3/4 in. NPT	SS4-AUV2-SS

Accessories SS4-AUV

	Part Number
Stainless steel swivel mounting assembly for FS24X, FS18X, SS4, SS2 detectors	SM4
0-20 MA module for SS4 detectors new version (factory installed)	MA420-4
Uv/ir test lamp with universal charger (FM and ATEX approval)	FT-2145
Sunshield for SS2, SS4 and FS24X detectors, 316 stainless steel	SH-001
Field of view restrictor	FVR-01
SS4 module HART (factory fitted, order with detector)	SS4-FSHCOM

Spare Parts SS4-AUV

	Part Number
Replacement electronics module for SS4-AUV2 (UV) detectors. Module only, non-latching LED	SS4-MOD-AUV2
UV test source module for SS4 detectors	H200
IR test lamp bulb for FT-2145/2045	LAMP-3135-0002
UV test lamp bulb for FT-2145/2045	DT-3124-0001A



SS3 Series

Fire and Flame Detectors for Safe Area (UV/IR)



The Model SS3-A (latching fire alarm relay) and SS3-AN (non-latching Fire Alarm relay) retain outstanding fire and flame detection capabilities in a non explosion-proof, ABS housing. This detector senses radiant energy in the ultraviolet (UV), visible and wide band infrared™ (IR) spectrum. The radiant energy from all types of flaming fires will alert the detector to their presence.

120° field of view with range up to 30 feet.

Features

- Multi-Spectrum™ senses energy in the ultraviolet, Visible and Wide Band Infrared™
- False alarm immunity
- Detects hydrocarbon and non-hydrocarbon fires
- Microprocessor based algorithms: FirePic™ and Tri-Mode Plot™
- Wide field-of-view
- FS2000™ System compatible or stand alone operation
- Compatible with approved fire alarm panels

SS3 Series

Part Number

UV/IR general purpose, safe area use detector, latching fire relay, FM and CSFM approval

SS3-A

UV/IR general purpose, safe area use detector, non-latching fire relay, FM and CSFM approval

SS3-AN

Accessories SS3

Part Number

UV/IR test lamp with universal charger (FM and ATEX approval)

FT-2145

IR test lamp bulb (FT-2145)

LAMP-3135-0002

UV test lamp bulb (FT-2145)

DT-3124-0001A

SS2-A Series

Digital Fire and Flame Detector (UV/IR)



The SS4 is a hazardous area certified flame detector for the detection of hydrocarbon (SS4-A2) and non-hydrocarbon fires (SS4-AS2). This multispectrum detector senses radiant energy in the ultraviolet (UV), visible and wideband infrared (IR) spectrum. The radiant energy from all types of flaming fires will alert the detector to their presence. The field of view is the widest in the industry with 120° field of view with a range of 60 ft. This means more hazard can be covered by each detector.

120° field of view with range up to 60 ft.

Features

- Multi-Spectrum™: senses ultraviolet, visible and Wide Band Infrared™
- Built-in test for optical “through the lens” testing
- False alarm immunity
- Detects hydrocarbon and non-hydrocarbon based fires
- Wide field-of-view and solar-blind
- Adjustable detector sensitivity
- Microprocessor based algorithms: FirePic™, Snapshot™ and Tri-Mode Plot™
- Wide temperature range of operation
- Compatible with standard approved fire alarm panels
- Explosion-proof housing
- Time programmable alarm verification

SS2-A Series

	Part Number
Copper-free aluminum housing UV/IR/VIS electro-optical fire detector, latching alarm relay, Class I, Div. 1, Groups B, C, & D, FM, CSFM, and cFM approved (2) 3/4 in. NPT	SS2-A
Copper-free aluminum housing UV/IR/VIS electro-optical fire detector, latching alarm relay, ATEX approved (2) M25	SS2-A-C-E
Copper-free aluminum housing UV/IR/VIS electro-optical fire detector, non-latching alarm relay, ATEX approved (2) M25	SS2-AN-C-E
Stainless steel housing UV/IR/VIS electro-optical fire detector, latching alarm relay, ATEX approved (2) M25	SS2-A-SS-C-E
Stainless steel housing UV/IR/VIS electro-optical fire detector, non-latching alarm relay, ATEX approved (2) M25	SS2-AN-SS-C-E
Copper-free aluminum housing UV/IR/VIS electro-optical fire detector, non-latching alarm relay, Class I, Div. 1, Groups B, C, & D, FM, CSFM, and cFM approved (2) 3/4 in. NPT	SS2-AN
Stainless steel housing UV/IR/VIS electro-optical fire detector, latching alarm relay, Class I, Div. 1, Groups B, C, & D, FM, CSFM, and cFM approved (2) 3/4 in. NPT	SS2-A-SS
Stainless steel housing UV/IR/VIS electro-optical fire detector, non-latching alarm relay, Class I, Div. 1, Groups B, C, & D, FM, CSFM, and cFM approved (2) 3/4 in. NPT	SS2-AN-SS

Accessories SS2-A

	Part Number
Stainless steel swivel mounting assembly for FS24X, FS18X, SS4, SS2 detectors	SM4
UV/IR test lamp with universal charger, (FM and ATEX approval)	FT-2145
Sunshield for SS2, SS4 and FS24X detectors, 316 stainless steel	SH-001
Field of view restrictor	FVR-01

Spare Parts SS2-A

	Part Number
SS2-A replacement electronics module	SS2-MOD-A
SS2-AN replacement electronics module	SS2-MOD-AN
IR test lamp bulb (FT-2145)	LAMP-3135-0002
UV test lamp bulb (FT-2145)	DT-3124-0001A



SS2-AM Series

Ultra-High Speed Digital Fire and Flame Detector (UV/IR)



The Model SS2-AM, (latching Fire Alarm relay), and SS2-AML (non-latching Fire Alarm relay), represent the world's pre-eminent Ultra-High Speed UV/IR technology for Electro-Optical Fire and Flame Detectors, with thousands successfully operating in a multitude of installations worldwide. This detector senses radiant energy in the Ultraviolet (UV), Visible and Wide Band Infrared (IR) spectrum. The radiant energy from all types of flaming fires will alert the detector to their presence.

120° field of view with range up to 60 feet.

Features

- Multi-Spectrum senses energy in the UV, Vis and WideBand IR™
- False alarm immunity
- Detects hydrocarbon and non-hydrocarbon fires
- Microprocessor based algorithms: FirePic™ and Tri-Mode Plot™
- Wide field of view and solar blind
- Wide temperature range of operation
- Explosion-proof housing
- FS2000™ System compatible or stand-alone operation
- Compatible with approved fire alarm panels

SS2-AM Series

Part Number

Copper-free aluminum housing UV/IR/VIS high-speed electro-optical fire detector, non-latching alarm relay, ALARM and FAULT relays, Class I, Div. 1, Groups B, C, & D, FM, CSFM, and cFM approved, 3/4 in. NPT

SS2-AM

Copper-free aluminum housing UV/IR/VIS high-speed electro-optical fire detector, latching alarm relay, ALARM and FAULT relays, Class I, Div. 1, Groups B, C, & D, FM, CSFM, and cFM approved, 3/4 in. NPT

SS2-AML

Accessories SS2-AM

Part Number

Stainless steel swivel mounting assembly for FS24X, FS18X, SS4, SS2 detectors

SM4

UV/IR test Lamp with universal charger, (FM and ATEX approval)

FT-2145

Sunshield for SS2, SS4 and FS24X detectors, 316 stainless steel

SH-001

Field of View Restrictor

FVR-01

Spare Parts SS2-AM

Part Number

SS2-AM replacement electronics module

SS2-MOD-AM

SS2-AML replacement electronics module

SS2-MOD-AML

Replacement housing copper-free aluminum base and top (white)

HA-SS2

IR test lamp bulb (FT-2145)

LAMP-3135-0002

UV test lamp bulb (FT-2145)

DT-3124-0001A

Model FS7

Multi-Spectral Infrared and Visible Electro-Optical Fire Detectors



The Fire Sentry FS7-2173 electro-optical radiant energy fire detector – and the Fire Sentry FS7-2173-2RP (unitized model) with multi-spectral WideBand IR™, Near Band IR and Visible Band fire detection are designed specifically for semiconductor Clean Room fire protection applications.

The Fire Sentry FS7 fire detector provides an intelligent two-stage response to semiconductor wet bench fires:

Stage 1: Alert. This is the first-stage response to a small fire with a heat energy output of 3 kW (the equivalent of a 4-inch diameter polypropylene pool fire). This allows time for the fire to self-extinguish.

Stage 2: Alarm. If the fire does not self-extinguish, and grows to the Factory Mutual specified heat energy threshold of 13 kW (the equivalent of an 8-inch diameter polypropylene pool fire), the second-stage response is activated.

Features

- Multi-Spectral digital electro-optical radiant energy infrared fire detector
- Unique two-stage fire detection response
- Immune to false alarm sources
- Not affected by absorbing smoke, gasses or chemical vapors
- Not sensitive to background radiant energy from electric heaters and ovens
- Detects hydrocarbon and non-hydrocarbon fires
- Rugged leak-proof, heat-sealed, acid-resistant, injection-molded polypropylene housing
- Wide 120° field-of-view
- Digital communication with RS-485 interface
- FirePic™; time and date-stamped digital fire signatures
- Built-in detector automatic self test
- Unitized model design for stand-alone operation

Model FS7

Multi-Spectral Infrared and Visible Electro-Optical Fire Detectors

FS7 Detectors	Part Number
Viton O-ring. For use with FS7-130-SX controller, FSWB control panel or S7-2175 control panel.	FS7-2173
Kal-rez O-ring. For use with FS7-130-SX controller, FSWB control panel or S7-2175 control panel.	FS7-2173-KALO
Non-latching alert and alarm relays. Viton O-ring.	FS7-2173-2RP
Non-latching alert and alarm relays. Kal-rez O-ring.	FS7-2173-2RP-K

FS7 Controller Systems	Part Number
Multi-zone compact controller, designed to be installed in fire panels, which monitors up to 12 Model FS7-2173 fire detectors. Programmable for up to 4 zones with relay outputs for ALERT and ALARM. Requires 24 Vdc. Approvals: FM & CSFM	FS7-130-SX
Single zone control panel which monitors up to 7 Model FS7-2173 fire detectors. Fire detectors plug directly into the control panel, which has a 24 hour battery back-up. Control panel has inputs for manual call stations, linear heat detectors, smoke detector and gas detectors. Outputs for suppression release for pulsed type solenoids and alarm annunciators. Requires 110 VAc. Approvals: FM	FSWB-1
Single zone control panel which monitors up to 7 Model FS7-2173 fire detectors. Fire detectors plug directly into the control panel, which has a 24 hour battery back-up. Control panel has inputs for manual call stations, linear heat detectors, smoke detector and gas detectors. Outputs for suppression release for pulsed type solenoids and alarm annunciators. Requires 24 Vdc. Approvals: FM	FSWB-3

Accessories	Part Number
Test Lamp. Battery operated for testing FS7 Fire Detectors up to 10 ft. distance.	FS-746-B
Test Lamp. Battery operated for testing FS7 Fire Detectors up to 2 ft. distance.	FT-S7
Junction box for connecting Model FS7-2173 fire detectors in a daisy chain or star configuration. Complete with (4) Lemo female connectors. Required for Model FS7-130-SX controller and Model S7-2175 control panel. Optional for other control panel applications.	FS7-2179
Polypropylene swivel mount. Allows fire detector to be pointed in any direction.	SM17
UV test lamp bulb (FT-2145)	DT-3124-0001A

FS7 - Interconnecting Cables	Part Number
5 ft. cable with male/male Lemo connectors (junction box to junction box)	CBMM-5
10 ft. cable with male/male Lemo connectors (junction box to junction box)	CBMM-10
20 ft. cable with male Lemo connector/open pigtail (junction box to Model FS7-130-SX controller or Model S7-2175 control panel)	CBMO-20
50 ft. cable with male Lemo connector/open pigtail (junction box to Model FS7-130-SX controller or Model S7-2175 control panel)	CBMO-50

Spare Parts	Part Number
Replacement PC board for FSWB controller	FSWB-MOD-4
110/220 VAc, 50-60 HZ input /15 Vdc output: universal charger for interface Box or DD Series, FT Series and TL Series test lamps	PSU-12

FS10 Fire Detection Systems

For Liquid and Powder Electrostatic Paint Booths



A high-speed microprocessor based fire detection and process control system specially designed for liquid and powder coating applications, the Fire Sentry FS System 10 quickly detects the presence of a flame, reacts by initiating a shutdown of the electrostatic finishing process in a matter of milliseconds; and effectively interrupts the fire before residues and wet paint films can ignite.

The Fire Sentry FS System 10 is the only system that provides a two-stage response: an ALERT for spray gun "fireball" type fires and if the fire continues, a FIRE ALARM is declared in 4-5 seconds.

90° field of view and detection range of 15 ft.

Features

- Multi-Spectral digital electro-optical infrared fire detector
- Meets requirements of NFPA 33
- Unique two-stage ALERT and FIRE ALARM response
- Immune to false alarms caused by arcs or corona discharges
- Built-in automatic "through the lens" self-test
- Not sensitive to background radiant energy sources such as paint heaters
- Not affected by absorbing smoke or paint solvent mist in liquid pant spray booths
- Sees through paint, powder or oil residue on detector's lens
- Digital communications with RS-485 interface
- FirePic™: retrieval of recorded pre-fire data
- SnapShot™: dynamic graphical display of what the detector sees

Wall Mount Controllers with FS10 Electro-Optical Fire Detector(s)

FS10 wall mount controller with fire detector(s) and 50 ft. of cable for each fire detector. Incl PC software, RS232 cable and manual. Meets NFPA 33

	Part Number
2 Fire Detectors 120 VAC	Option-1-GF
2 Fire Detectors 220 VAC	Option-1-240-GF
1 Fire Detector 120 VAC	Option-1S-120-GF
1 Fire Detector 220 VAC	Option-1S-240-GF

Card Controller with FS10 Electro-Optical Fire Detector

FS10 fire detector with card controller. Incl PC software and manual.

Note: Requires backplane card and 24 Vdc.

	Part Number
2FL system: liquid paint spray line applications w / two (2) fire signal relay levels	Option-2FL
2GF system: general finishing applications w/process control and fire alarm signal relays	Option-2GF
2WE system: powder coating and paint spray line applications w / two (2) fire signal relay levels	Option-2WE
2WL system: paint spray line applications w/three (3) fire signal relay levels	Option-2WL
Backplane for 1 card controller	BP-1
Backplane for 2 card controllers	BP-2
Backplane for 4 card controllers	BP-4

FS10 Fire Detection Systems

For Liquid and Powder Electrostatic Paint Booths

Spare Parts - FS10 Wall Mount Controller and Card Controller	Part Number
Model FS10 wall mount controller. Specify if for (1) or (2) detectors	FS10-CONT
Model FS10 wall mount controller. For (1) detector	FS10-CTL-1S
Model FS10 wall mount controller. For (2) detectors	FS10-CTL-2
Replacement electronic PC board for FS10 wall mount controller for 1 detector	FS10-MOD-CTL-1
Replacement electronic PC board for FS10 wall mount controller for 2 detectors	FS10-MOD-CTL-2
Replacement keypad for FS10 wallmount	SW-5143-001
FS10 card controller, XX = version, i.e., GF	FS10-CARD-2XX
Model FS10 fire detector for use with wall mount controller or card controller	FS10-DETECTOR
Replacement electronics module for fire detector for the above systems <i>Note: State serial number of module to be replaced at time of order</i>	FS10-DET-MODULE

Detector Cables	Part Number
Fire detector cable available in 10 ft. increments. (XX = specify length in feet)	CAB-XX
50 ft. card controller cable. Connects fire detector to controller	CAB-50
100 ft. card controller cable. Connects fire detector to controller	CAB-100

FS10 Stand Alone (Unitized) Electro-Optical Fire Detectors	Part Number
Includes ALARM and FAULT relays. 24 Vdc input. Temperature range (-40°C to +85°C). Approvals: FM, cFM, CSFM for Class I, Div. 2, Groups B, C, & D.	
Copper-free aluminum housing incl ALERT / FIRE EARLY WARNING relay, 30 ft. sensitivity (latching alert and alarm relays)	FS10-R30
316 stainless steel housing incl ALERT / FIRE EARLY WARNING relay, 30 ft. sensitivity (latching alert and alarm relays)	FS10-R30-SS
Copper-free aluminum housing 45 ft. sensitivity (latching alarm relays)	FS10-R45
316 stainless steel housing 45 ft. sensitivity (latching alarm relays)	FS10-R45-SS
Copper-free aluminum housing incl ALERT / FIRE EARLY WARNING relay, 30 ft. sensitivity (non-latching alert and alarm relays)	FS10-RN30
316 stainless steel housing incl ALERT / FIRE EARLY WARNING relay, 30 ft. sensitivity (non-latching alert and alarm relays)	FS10-RN30-SS
Copper-free aluminum hsg 45 ft. sensitivity (non-latching alarm relays)	FS10-RN45
316 Stainless steel housing 45 ft. sensitivity (non-latching alarm relays)	FS10-RN45-SS

FS10 Fire Detection Systems (continued)

Spare Parts - FS10 Stand Alone (Unitized) Electro-Optical Fire Detectors	Part Number
Replacement electronics module for Model FS10-R30 stand alone fire detector (latching alert and alarm relays)	FS10-R30-MOD
Replacement electronics module for Model FS10-R45 stand alone fire detector (latching alarm relay)	FS10-R45-MOD
Replacement electronics module for Model FS10-RN30 stand alone fire detector (non-latching alert and alarm relays)	FS10-RN30-MOD
Replacement electronics module for Model FS10-RN45 stand alone fire detector (non-latching alarm relay)	FS10-RN45-MOD

Spare Parts - FS10 Stand Alone (Unitized) Electro-Optical Fire Detectors	Part Number
Stainless steel grill kit for FS10-R and FS10-CS detectors (Killark housing) kit includes: (1) SS grill, (2) SS brackets, and (2) SS screws	FS10R-GR-KIT
RS485 computer cable for connection from fire detector to interface box	FS10R-CABLE-DET
Interface kit, complete with interface box, cables, 100-240 V _{AC} / 12 V _{DC} universal charger and software. Used for interrogating the FS10R/A fire detector	FS10R-IK
Interface box used for interrogating FS7-2173-2RP/FS10R fire detectors (includes universal charger)	PCI-24
RS232 computer cable for connection from FS7-130-SX, S7-2175, option-1 or option-2 controllers or interface box to PC	RS-232 CABLE
PC software (Windows version) for FS10 stand alone interface box	W-FS10R-SW
110/220 V _{AC} , 50-60 HZ input /15 V _{DC} output : universal charger for interface box or DD Series, FT Series and TL Series test lamps	PSU-12

Accessories - FS10 Stand Alone (Unitized) and Controller Based Electro-Optical Fire Detectors	Part Number
Stainless steel swivel mount allows detector to be pointed in any direction	SM4
Test lamp battery operated for testing FS10 fire detectors up to 10 ft.	FS-846-B
Disposable protective covers keeps powder or paint off the window lens of the FS10 fire detector (12 per bag)	DPC-12
Air shield for powder applications protects FS10 fire detector window lens from powder build-up. Supplied with fitting for 1/4 in. tubing	DASA1-P
Air shield for powder applications protects FS10 Fire Detector window lens from powder build-up. Supplied with fitting for 6 mm tubing	DASA6-N
Key for wall-mount controller panel	HD-CTL-KEY
Field of view restrictor	FVR-01

Honeywell Analytics Service



Honeywell Analytics' global standing for portable, fixed and low level toxic gas detection is backed up with a dedicated team of professionals that takes service and support to a whole new level.

It's your choice...

Whatever industry you're in, we have the levels of support that are right for your business.

It's your business. It's your industry.

And no matter whether you're managing personnel for confined space entry, or securing your plant against gas risks, the process has to keep moving. The alternative is downtime, or even total shutdown, and then the risks to your business are far greater.

Honeywell provides service levels that make it easy to choose the right kind of support to keep your plant and people safe; to keep your business up and running - because that's our job!

Choose from:

Installation and Commissioning

- Installation, configuration and commissioning
- Functional tests
- Start-up
- Staff training
- Bump testing

Contract Maintenance

Service and Repair

- On-site/workshop repair and calibration
- Modification and conversion

Calibration and Surveys

- Instrument calibration equipment certified to national/regional standards
- Site surveys
- Stock surveys

Honeywell Analytics Service contact information:

USA Service Workshop

Honeywell Analytics
405 Barclay Blvd.
Lincolnshire, IL 60069
USA

Tel: 800-538-0363 (option #5)
E-mail: ha.us.service@honeywell.com

Canada Service Workshop

3580 Rue Isabelle Unit 100
Brossard, Quebec, Canada
J4Y 2R3

Tel: 1-800-563-2967 (select language + press 2)
Email: haservice.canada@honeywell.com

Notes



Honeywell Analytics Lines of Business



Commercial

Gas detection from standalone units to fully engineered, multi-point systems, all offering cost-effective regulatory compliance

- » Applications: parking structures, chillers, mechanical rooms, office towers, commercial buildings, shopping centers, swimming pools, golf courses, schools and universities, laboratories

Industrial

Renowned Sieger and Manning gas detection systems with advanced electrochemical, infrared and open path sensing technologies

- » Applications: oil and gas, cold storage, water/wastewater treatment, chemicals, engine rooms, plastics and fibers, agriculture, printing and light industrial

Portables

Single or multi-gas and other premium detectors with compact, lightweight designs ranging from simple alarm only units to advanced, fully configurable and serviceable instruments

- » Applications: underground utility and electricity ducts, boiler rooms, post-fire sites, sewers, industrial plants, industrial hygiene, first responder teams, remote fleets

Find out more

www.honeywellanalytics.com

Contact Honeywell Analytics:

USA

Honeywell Analytics, Inc.
405 Barclay Blvd.
Lincolnshire, IL 60069
USA

Canada

2840 2nd Ave SE
Calgary, Alberta, Canada
T2A 7X9

3580 Rue Isabelle Unit 100
Brossard, Quebec, Canada
J4Y 2R3

Toll free: 1-800-538-0363

Tel: 1-847-955-8200

Fax: 1-847-955-8210

HA_customerservice@honeywell.com

Technical Services

Tel: 1-800-538-0363 (option #5)

ha.us.service@honeywell.com

www.honeywell.com



High Tech/Government

A complete portfolio of gas and chemical detection instrumentation including infrared spectroscopy (MST) with no cross interference, to Chemcassette paper-based solutions (MDA Scientific) offering detection down to parts per billion

- » Applications: semiconductor manufacturing and nanotechnology, aerospace propulsion and safety, specialty chemicals industry, research laboratories, emergency response

Technical Services

24/7 global network includes post-sales service and Systems Integration teams

- » Emergency call out, service contracts, on/off-site repair, training and commissioning
- » Complete range of spares, consumables and accessories

Europe, Middle East, Africa

Life Safety Distribution AG

Weiherrallee 11a

CH-8610 Uster

Switzerland

Tel: +41 (0) 44 943 4300

Fax: +41 (0) 44 943 4398

gasdetection@honeywell.com

Asia Pacific

Honeywell Analytics, Asia Pacific

#508, Kolon Science Valley (1)

187-10 Guro-Dong, Guro-Gu

Seoul, 152-050

Korea

Tel: +82 2 6909 0300

Fax: +82 2 2025 0328

analytics.ap@honeywell.com

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

PG6670-1-NCL
© 2013 Honeywell Analytics

Honeywell